



MULTI WORK TUBE FURNACES



- Our VTF range comprises 9 models with a minimum of 1 and a maximum of 4 tubes as standard. Our VTF range has a maximum working temperature of 1600°C (2912°F).
- All Vecstar tube furnaces are compatible with our range of Gas Tight Ends.
- Please review the information displayed below to find the most suitable furnace for your needs, then contact us for a quote.

ABOUT VECSTAR

We build furnaces, ovens and hot plates for industry, laboratories and educational institutions. During the 30+ years Vecstar have been established, a comprehensive range of advanced electric heating equipment has been developed.

CONTACT US

W: www.vecstar.com

E: info@vecstar.com

UK Tel:

+44 (0)1246 260094

USA Tel:

1-877-842-4652 (Toll Free)

ADDRESS

Head Office Address:

Units 11 & 12

Foxwood Road

Dunston Trading Estate

Chesterfield

S41 9RF

Model	Max Temp	Max. continuous working temperature	Chamber Diameter (mm)	Heated Length (mm)	External Dimensions (mm)			Work Tubes	Power (kW)	Holding Power (kW)	T/C Type
					Height	Width	Depth				
VTF1	1200°C	1150°C	25	150	560	400	340	1	1.5	0.6	K
VTF2	1200°C	1150°C	25	150	560	400	340	2	1.5	0.6	K
VTF3	1200°C	1150°C	25	150	560	400	340	4	1.5	0.6	K
VTF4	1400°C	1400°C	25	150	710	470	410	1	2.25	0.9	R
VTF5	1400°C	1400°C	25	150	710	470	470	2	2.25	0.9	R
VTF6	1400°C	1400°C	25	150	780	470	470	4	2.25	0.9	R
VTF7	1600°C	1600°C	25	150	550	520	460	1	3.5	1.4	R
VTF8	1600°C	1600°C	25	150	770	520	520	2	3.5	1.4	R
VTF9	1600°C	1600°C	25	150	830	520	520	4	3.5	1.4	R